

# DIRT DRIVER

**TAMPERPROOF**



**STATIC HOT AND COLD POWER WASHERS**

# Tamperproof Static Hot & Cold Water Washers

The "TAMPERPROOF" Static Hot & Cold Power Washer is housed in a strong lockable cabinet manufactured from either Zintec or Stainless Steel, and all models would normally be frost protected.

The "Tamperproof" can be supplied in varying pressures & volumes from the standard Single Phase 1500 psi @ 12 Litres per minute through to the Three Phase Models - i.e. 2200psi @ 15 LPM ; 2300psi @ 18 LPM or 3000 psi @ 15 LPM - all available for either Manual Push Button Control or Automatic Token Control.

## CUSTOM BUILD

Due to the nature of our production facilities - we can custom build units to any specification - i.e. Special sizes; different pumps or motors; with Remote Control - all available in Painted Zintec or Stainless Steel.

## OPTIONS AVAILABLE

- Single or Twin Cabinets
- Internal Hose Reels
- Flame Failure Cut Out
- Larger coils for increased heat
- Insulated Cabinets
- Remote Controls
- Fleet Colour Scheme

## MANUAL "TAMPERPROOF"

- Push Button Control
- Timed Shutdown
- On/Off High Pressure Chemical
- Available in Painted Zintec or Stainless Steel

## AUTOMATIC "TAMPERPROOF"

- Token Control
- Adjustable Time Settings
- CYCLE 1 - Hot Water & Detergent
- CYCLE 2 - Cold Water or Hot Water Rinse
- No Circuit Board Control
- Available in Painted or Stainless Steel
- Manual Over-ride



Twin Tamperproof Unit

## Features standard to both models:

- \* 24 v switching for operator safety
- \* Thermostatically controlled heat
- \* Low fuel warning
- \* Low water warning
- \* Lockable control panel door for anti-vandalism
- \* Thermal overload protection
- \* Emergency stop button
- \* Anti-tangle hose
- \* Insulated chimney & rain cap

Specification	Model 100/12	Model 150/14	Model 200/15	Model 160/18
Pump output	1500psi/100bar	2200psi/150bar	3000psi/200bar	2300psi/160bar
Water consumption	12 LPM	15 LPM	15 LPM	18 LPM
Electric motor	2.2KW/230V/50	4.0KW/400V/50	5.5KW/400V/50	5.5KW/400V/50
Jet supplied	15 Degree	15 Degree	15 Degree	15 Degree
Jet sizes available	15/25/40 Degree	15/25/40 Degree	15/25/40 Degree	15/25/40 Degree
Water inlet	12.5mm	12.5mm	12.5mm	12.5mm
Input cable	NOT SUPPLIED UNLESS SPECIFICALLY REQUESTED			
Water temperature	80/100 C	80/100 C	80/100 C	80/100 C
Weight	250KGS	255KGS	270KGS	270KGS
Dimensions	147 x 84 x 54	147 x 84 x 54	147 x 84 x 54	147 x 84 x 54
Chimney	65 cms	65 cms	65 cms	65 cms

Manufactured for and distributed by:



Demonstration without obligation

We reserve the right to amend specification of our equipment and our accessories without prior notification